

GYLON EPIX® Style 3510

Case Study: Monomer production



Industry

Chemical

Customer

Monomer Producer

Background

The customer is a producer of monomers and other feed stocks for the manufacture of coatings, adhesives and sealants.

Challenges faced

The customer's maintenance personnel had been using virgin PTFE and spiral wound gaskets but with no predictable reliability. Leakage issues, prompted the search for better sealing solutions. Ideally they desired one gasket to be used in all applications which included monomers, strong caustics and acids.

Operating Conditions

1. Media: Meth-acrylic, acrylic, hypo-phosphorous, 25% sodium hydroxide which is diluted 50% with water and methanesulfonic acid (MSA). MSA is considered particularly aggressive
2. Temperature: 10 - 21 °C
3. Pressure: 50 psig to 60 psig (3.4 bar-g to 4.1 bar-g)
4. Size: Nominal pipes sizes of 1", 1-1/2", 2", 3", and 4"

Solution and Benefits

GYLON EPIX® Style 3510 was installed and is still performing reliably and without leaks.

GYLON EPIX® 3510 has helped to decrease the number of gaskets needed to seal the range of service conditions.

For more information, please visit:

www.garlock.com

GARLOCK GMBH

an Enpro Company

Falkenweg 1, 41468 Neuss, Germany

+49 2131 349 0

garlockgmbh@garlock.com

www.garlock.com

Garlock Sealing Technologies

Garlock USA

Garlock Australia

Garlock Canada

Garlock China

Garlock Germany

Garlock India

Garlock de México

Garlock New Zealand

Garlock Singapore